





EL-TECH 230He ELECTRICALLY CONDUCTIVE EPOXY ADHESIVE

PRODUCT DESCRIPTION

EL-TECH 230He is a silver filled, two component, heat curing, 1 to 1 mix ratio, easy to use electrically conductive %100 solid epoxy adhesive with excellent solvent resistance properties. Product is designed for bonding electronical and mechanical attachments on electronic devices. Results excellent conductivity in microelectronic and optoelectronic applications.

CURING PROPERTIES

80°C	120°C	150°C	175°C
90 min.	15 min.	5 min.	45 sec.
Pot Life: 4 days @21°0	C		

UNCURED PROPERTIES

	Part A	Part B
Color	Silver	Silver
Viscosity	Paste like	Paste Like
Mix Ratio(by weight)	1	1

CURED PROPERTIES

Volume Resistivity (Ω-cm)	0.0001 to 0.0004	
Thermal Conductivity (W/mK)	6,5	
Tg (°C)	115	
Tensile Shear Strength (N/mm²)	10,5	
Specific Gravity	2,6	
Temperature Resistance (°C)	-55 - +200	

INSTRUCTIONS FOR USE

Mix Parts A and B in original container before combining. Add Part B to Part A and mix until uni-form. Shelf life is 12 months at 25°C, in unopened, unmixed containers.



